

**DK**

**DeMenno Kerdoon**

**MATERIAL SAFETY DATA SHEET – MSDS**

Revision No. : 2  
Original Issue Date: 10/13/03

Revision Date : 10/13/03  
Last Review Date : 10/23/00  
MSDS Page One

**TRINITY N512P PREDILUTED LONG LIFE ANTIFREEZE(50%)**

MSDS No. 101303.2    Warning! May cause irritation. Contains ethylene glycol. Harmful or fatal if swallowed. May cause damage to brain, kidney or liver. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash area thoroughly after handling. For industrial use only; not for household use.

Date            08/18/03

Emergency Number v: Chemtrec : 800/424-9300  
General Information : DEMENNO KERDOON (310) 537-7100

**SECTION I - IDENTIFICATION**

Product :                    Trinity Pre-dilute Long Life Coolant N512P  
  
Synonyms :                 DK N512P Long Life Pre-diluted Antifreeze Formulation  
  
Chemical Family :        Ethylene Glycol solution of salts  
  
CAS RN :                    Mixture - no single CAS number applicable

**SECTION II – INGREDIENTS**

<b>Components</b>	<b>CAS RN</b>	<b>Nominal %</b>	<b>PEL/TLV</b>	<b>Hazard</b>
Ethylene Glycol	107-21-1	40-55%	Ceiling : 50 ppm  (125 mg/m)  [vapor and damage. Mist]	Respiratory irritant Ingestion may produce liver, brain and kidney
Diethylene glycol	111-46-4	Less than 5%	None	Ingestion may produce liver and kidney damage.

DeMenno Kerdoon  
2100 North Alameda Street  
Compton, CA 90222

Telephone: (310) 537-7100  
Fax: (310) 639-2946

**SECTION II – INGREDIENTS**

<u>Components</u>	<u>CAS RN</u>	<u>Nominal %</u>	<u>PEL/TLV</u>	<u>Hazard</u>
Hydrated inorganic acids, organic acid salts	proprietary	Less than 5%	PEL-TWA :  5 mg/m  TLV-TWA : inflammation. 5 mg/m	Skin, eye and respiratory irritant. GI tract salts and
Water	7732-18-5	Less than 50%	None	None noted.

**SECTION III - HEALTH INFORMATION**

Inhalation: Breathing excessive levels of the vapor or mist can irritate the respiratory tract. Excessive vapor concentrations of the major component (ethylene glycol), as might be generated during heating of this material, have occasionally been reported to cause adverse effects on the blood-forming system and the nervous system.

Ingestion: The acute oral toxicities of the components of this mixture are as follows :

Ethylene Glycol: The lowest dose reported to produce death in humans was estimated to be 710 mg/kg body weight; for a person weighing 150 pounds, this would be equivalent to drinking about one and one-half (1.5) fluid ounces of pure ethylene glycol in a short period of time.

Acute oral LD50's = 4,700 mg/kg (rats)  
7,500 mg/kg (mice)  
2,000 mg/kg (cats)

Hydrated Inorganic Acid, Sodium Salt: The lowest dose of a similar compound reported to produce death in humans was estimated to be 709 mg/kg body weight; for a person weighing 150 pounds, this would be equivalent to swallowing about one-tenth (.1) of a pound of the dry material in a short period of time.

Acute oral LD50's  
For a similar compound = 2,660 mg/kg (rats)  
2,000 mg/kg (mice)



**SECTION VI - PHYSICAL DATA**

Boiling Point: 226 degrees F  
Melting Point: Not Determined  
Vapor Pressure: Not Determined  
Specific Gravity (60/60 F): 1.088  
Vapor Density (AIR = 1): Not determined  
pH (30% water solution): 7.9  
Solubility in Water: Infinitely miscible  
Appearance and Color: Clear, slightly viscous, orange colored liquid

**SECTION VII - FIRE AND EXPLOSION HAZARDS**

Flash Point: > 40% water; none  
Auto-Ignition Temperature : Not determined (752 F for ethylene glycol)

Flammable Limits in Air, %by Vol. Lower : Not determined (3.2% for ethylene glycol)  
Upper : Not determined (15.3% for ethylene glycol)

NFPA Rating : Health (1) Fire (1) Reactivity (0) NFPA Rating  
(Does not apply to exposure hazards other than during a fire.) Major  
component (Ethylene glycol) has ratings of Health (1), Fire (1), and Reactivity (0).

Fire Fighting Procedures: (Note: Individuals should perform only those firefighting procedures for which they have been trained.)

Use water spray, dry chemical, foam or carbon dioxide. Use water to keep fire-exposed containers cool. If a spill or leak has not ignited, use water spray to disperse the vapors. Water spray may be used to flush spills away from fire and diluted spills to noncombustible proportions (see warning on water spray on hot glycol below).

Unusual Fire & Explosion Hazards: Fire fighters should wear self-contained breathing apparatus in the positive pressure mode with a full face piece when, there is a possibility of exposure to smoke, fumes or hazardous decomposition products. Water spray may cause foaming of hot glycol so indirect application of water spray or use of other extinguishing media should be used on hot glycol.

**SECTION VIII – REACTIVITY**

Stability: Generally stable

**DK**

**DeMenno Kerdoon**

Hazardous Polymerization: Not likely to occur

MSDS NO. 101303.2

MSDS Page Five  
FORMULA N512P

Conditions and Materials to Avoid: Avoid concentrated strong acids, oxidizing agents and bases.  
Do not expose to open flame.

Hazardous Decomposition Products: If pyrolyzed, thermal decomposition products of residue may include C, CO, CO<sub>2</sub>, H<sub>2</sub>O, NH<sub>3</sub>, organic vapors and nitrogen-containing.

### **SECTION IX - EMPLOYEE PROTECTION**

Control Measures: Handle in the presence of adequate ventilation. Engineering controls should be used whenever feasible to maintain concentrations below acceptable exposure criteria (see Section II and IV), including enclosures and local exhaust ventilation.

Respiratory Protection : Where exposure is likely to exceed acceptable criteria (see Section II and IV) and engineering controls are not feasible, use NIOSH/MISHA approved respiratory protection equipment. Respirators should be selected based on the form and concentration of contaminants in air and in accordance with OSHA (29 CFR 1910.134).

Protective Clothing: Wear gloves and protective clothing which are impervious to the product for the duration of exposure if there is potential for skin contact.

Eye Protection: Wear safety glasses meeting the specifications of ANSI standard Z87.1 where no contact with the eye is anticipated. Chemical safety goggles meeting the specification of ANSI Standard Z87.1 should be worn whenever there is the possibility of splashing or other contact with the eyes.

### **SECTION X - ENVIRONMENTAL PROTECTION**

Environmental Precautions: Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill release response plan should be developed and implemented.

Spill or Leak Procedures: Wear appropriate respiratory equipment and protective equipment as described in Section IX. Contain spilled material. Transfer to secure containers.  
Where necessary, collect using absorbent media. In the event of an uncontrolled release is reportable under the applicable laws and regulations.

DeMenno Kerdoon  
2100 North Alameda Street  
Compton, CA 90222

Telephone: (310) 537-7100  
Fax: (310) 639-2946

MSDS NO. 101303.2

MSDS Page Six  
FORMULA N512P**SECTION X - ENVIRONMENTAL PROTECTION**  
**(Continued)**

Waste Disposal: All recovered material should be packaged, labeled, transported, and disposed of or reclaimed in conformance with good engineering practices. Avoid land filling of liquids. Reclaim where possible.

**SECTION XI - REGULATORY CONTROLS**

Department of Transportation :

DOT Classification : Class 9 miscellaneous

DOT Proper Shipping Name : Other regulated substances, liquid, n.o.s. (ethylene glycol), Class 9, UN 3082, PG III, RQ (ethylene glycol)

Other Regulatory Requirements:

Toxic Substance Control Act: This product is listed in the TSCA Inventory of Chemical Substances. All of the components of the mixture are listed in the TSCA Inventory of Chemical Substances.

SARA Hazard Categories (as defined in Section 3111/312)

Immediate/Acute Health Hazard: Delayed/Chronic Health Hazard

The product contains greater than 85 % ethylene glycol (CAS #107-21-1) which is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Clean Air Act (1990) – List of Hazardous Air Contaminants: Listed

CERCLA: Reportable Quantity (RQ): 5,000 pounds

State Right-to-know:

California – Exposure limits-Ceilings: vapor-50 ppm ceiling: 125 mg/m<sup>3</sup> ceiling

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): This product chemical(s) known to the State of California to cause birth defects and or other reproductive harm.

<u>Component</u>	<u>CAS #</u>	<u>Amount</u>
Ethylene glycol monomethyl ether	109-86-4	<=.0009%

California SCAQMD Rule 443.1 Labeling of materials containing organic solvents

VOC: Vapor pressure 0.06 mmHG at 20 degrees C

**SECTION XII - PRECAUTIONS: HANDLING, STORAGE AND USAGE**

- To prevent possible storage container rupture, do not permit to freeze; See section VI.
- Do not expose children and pets to this material.
- Keep container closed.
- Keep away from open flames
- After handling product, wash thoroughly with soap and water before drinking, eating, or smoking.
- Container hazardous when emptied. Since emptied containers retain product residues, all hazardous precautions described on this MSDS must be observed.

**SECTION XIII - CONTACT INFORMATION**

The information presented herein is believed to be factual as it has been derived from the works and opinions of people believed to be qualified experts; however, nothing contained in this information is to be taken as a warranty or representation for which DeMenno Kerdoon Corporation bears legal responsibility. The user should review any recommendation in the specific context of intended use to determine whether they are appropriate.

Prepared By DeMenno Kerdoon Corporation

For further information contact:  
Environmental Manager  
DeMenno Kerdoon Corporation  
2000 North Alameda Street.  
Compton, CA 90222  
(310) 537-7100